



ZM56 Specifications

Data Rate	300 bps up to 56k bps, V.90																		
RS-232 Baud Rates	1200 to 115.2k Baud																		
Configuration	Hayes AT [®] style command structure																		
Interface	RS-232 DB9 female connector																		
Phone Line	RJ11C connector																		
Power (5 to 30 Vdc)	<table border="1"> <thead> <tr> <th></th> <th>Idle</th> <th>Connected (typical values)</th> </tr> </thead> <tbody> <tr> <td>5Vdc</td> <td>68mA</td> <td>82mA</td> </tr> <tr> <td>8Vdc</td> <td>44mA</td> <td>53mA</td> </tr> <tr> <td>12Vdc</td> <td>32mA</td> <td>38mA</td> </tr> <tr> <td>24Vdc</td> <td>20mA</td> <td>22mA</td> </tr> <tr> <td>30Vdc</td> <td>17mA</td> <td>19mA</td> </tr> </tbody> </table> Removable 3-pin connector		Idle	Connected (typical values)	5Vdc	68mA	82mA	8Vdc	44mA	53mA	12Vdc	32mA	38mA	24Vdc	20mA	22mA	30Vdc	17mA	19mA
	Idle	Connected (typical values)																	
5Vdc	68mA	82mA																	
8Vdc	44mA	53mA																	
12Vdc	32mA	38mA																	
24Vdc	20mA	22mA																	
30Vdc	17mA	19mA																	
Operating Temperature Range	-40°C to +85°C 10% to 90% RH (non-condensing)																		
Auto-Dial Capability	Up to 3 Dial-out numbers. Programmable retries for each number. 512 character message string. Dry contact trigger or voltage input (5 – 30Vdc) LED progress and status indications.																		
Size	5.0 in. x 5.0 in. x 1.45 in.																		

Hayes AT[®] is a registered trademark of Hayes Microcomputer Products, Inc.